Automation ISCAR Metalworking Automation New Threading New MILLING Maching Threading New Milling Maching Threading New Milling Maching New Milling New

SLOTTING

62-2024

DECEMBER 2024

METRIC



















SLOTTING

62-2024

New Product Announcement

DECEMBER 2024

METRIC







New Cylindrical Solid Carbide Shanks with an Internal Coolant Channel



Shank Features

T-SLOT tools with exchangeable milling heads. These new shanks feature a central coolant channel that branches out to each flute of the milling heads. The new coolant method effectively reaches the cutting zones and substantially increases tool life. The new shanks are available with the standard **T-SLOT** SP connections, including SP11, SP13, SP15, SP17, and SP19 types. These new shanks provide highly rigid clamping for **T-SLOT** milling heads. The combination of the new solid carbide shanks and the large assortment of **T-SLOT** heads opens the door for new opportunities.



PAGE 2 / 3






SLOTTING

62-2024

DECEMBER 2024

METRIC

SD S-A-C-H-SP Stepped Cylindrical Carbide Shanks with Brazed Steel Segment for Interchangeable Solid Carbide Milling Heads https://www.iscar.com/eCatalog/Family.aspx?fnum=5483&mapp=ML&GFSTYP=M&srch=1



Designation	DCONMS	DCONWS	THSZWS	LDRED	LB	LF	OAL	Shank m.	© kg
SD S-A-L110-C16-C-H-SP11	16.00	11.00	M4x0.5	10.5	14.83	110.00	113.85	С	0.30
SD S-A-L130-C16-C-H-SP13	16.00	13.00	M4x0.5	13.0	16.57	130.00	134.35	С	0.35
SD S-A-L130-C16-C-H-SP15	16.00	15.00	M5x0.5	16.0	18.18	130.00	134.90	С	0.35
SD S-A-L140-C20-C-H-SP17	20.00	17.00	M6x0.5	20.2	23.77	140.00	146.00	С	0.60
SD S-A-L160-C25-C-H-SP19	20.00	17.00	M6x0.5	20.2	24.58	160.00	168.50	С	1.10

Apply lubricant to the clamping screw

Spare Parts			0
Designation	Screw	Torx Blade	T-Handle
SD S-A-L110-C16-C-H-SP11	SR M4X0.5-SP11 HG	BLD T15/S7	SW6-T-SH
SD S-A-L130-C16-C-H-SP13	SR M4X0.5-SP13-IP15-HG	BLD IP15/S7	SW6-T-SH
SD S-A-L130-C16-C-H-SP15	SR M5X0.5-SP15-IP20-HG	BLD IP20/S7	SW6-T-SH
SD S-A-L140-C20-C-H-SP17	SR M6X0.5-SP1719-IP25-HG	BLD IP25/S7	SW6-T
SD S-A-L160-C25-C-H-SP19	SR M6X0.5-SP1719-IP25-HG	BLD IP25/S7	SW6-T

